




# BLANKET WARMERS

**NULINE**  
REFRIGERATION

## FEATURES

- Fan Forced System
- Overheating Alarm
- Safety Cutoff at 70°C
- Double Glazed Doors
- Stainless int./ext. with Chrome Plated Shelves
- Microprocessor Control
- Digital Display with High Alarm
- TGA Certified



	60°C
	80 L 211 L 611 L 1000 L
	500w x 575d x 625h 850w x 575d x 965h 750w x 700d x 1865h 1200w x 700d x 2100h

+61 3 9562 3355  
info@nuline.au  
7 Longford Court, Springvale VIC 3171  
[www.nulinerefrigeration.com.au](http://www.nulinerefrigeration.com.au)



# BLANKET WARMERS



Model	BW100	BW250	BW650	BW1100
Gross Capacity	80 L	211 L	611 L	1000 L
Blanket Capacity	5 - 6	10 - 12	30 - 35	47 - 52
External Dimensions in mm (w/d/h including castors)	500 x 575 x 625	850 x 575 x 965	750 x 700 x 1865	1200 x 700 x 2100
Internal Dimensions in mm (w/d/h)	390 x 480 x 430	740 x 485 x 590	630 x 610 x 1590	1100 x 550 x 1555
Packed Dimensions in mm (w/d/h including pallet)	575 x 670 x 765	920 x 675 x 1255	820 x 820 x 2185	1300 x 800 x 2250
Gross Weight - kg (packed weight)	82	133	182	137
Net Weight - kg	75	125	175	125
Voltage	240V			
Temperature Range	60°C			
Exterior Cabinet Finish	Stainless Steel			
Inner Liner Material	Stainless Steel			
Door	Glass			
Door Hinge	RH	LH / RH	RH	LH / RH
Door Handle	Full Length			
Type of Controller	Microprocessor			
Temperature Display	Digital			
BMS Connectivity (BMS Connectivity for Remote Alarms only)	Optional			
(BMS Connectivity for 4-20mA Transmitter)	Optional			
Port Entry	Optional			
Castors	Fixed Legs		Yes	
Adjustable Shelves	2	3		6
Usable Shelf Area in mm(w/d)	390 x 480	740 x 480	630 x 610	1000 x 530



Nuline Refrigeration reserves the right to alter the specifications without prior notice.