

HRF 400 2T COMBINATION

NULINE
REFRIGERATION

FEATURES

- Digital display
- Hi/Lo Readout
- Remote alarm contacts
- Door locks
- Separate refrigeration systems for each unit
- Data logger provided for refrigerator
- TGA Certified



Refrigerator: 2°C to 8°C
Freezer: -18°C to -22°C



135 L – for both
Refrigerator and Freezer



595w x 650d x 1720h

+61 3 9562 3355
info@nuline.au
7 Longford Court, Springvale VIC 3171
www.nulinerefrigeration.com.au



HRF 400 2T COMBINATION



Model	Refrigerator	Freezer
Gross Capacity	135 L	135 L
External Dimensions in mm (w/d/h including castors)	595 x 650 x 1720	
Internal Dimensions in mm (w/d/h)	455 x 445 x 665	
Packed Dimensions in mm (w/d/h including pallet)	640 x 670 x 1895	
Gross Weight - kg (packed weight)	90	
Net Weight - kg	85	
Voltage	240V	
Energy Consumption	402 kWh/y	
Temperature Range	2°C to 8°C	-18°C to -22°C
Ambient Temperature Range	10°C to 32°C	
Refrigerant	R600a	
Cooling System / Defrost	Fan Forced / Automatic	Static / Manual
Exterior Cabinet Finish	Enamelled Steel	
Inner Liner Material	ABS	
Door	Glass	Solid
Door Hinge	RH	
Door Handle	Pull Handle	
Type of Controller	Digital	
Temperature Display	External	
Data Logger	Included	Optional
Door Ajar Alarms	Optional	
High and Low Readout	Visual / Audible	
BMS Connectivity		
(BMS Connectivity for Remote Alarms only)	Yes	
(BMS Connectivity for 4-20mA Transmitter)	Optional	
Port Entry	Optional	
Battery Back-up for Controller	Optional	
Power Requirement	10amp GPO	
Watts	81W	75W
Castors	Yes	
Adjustable Shelves	Yes	Fixed
Usable Shelf Area in mm(w/d)	2 x Large Shelves 455 x 405 2 x Small Shelves 438 x 202	2 x Large Shelves 455 x 405
Light	LED	



Nuline Refrigeration reserves the right to alter the specifications without prior notice.